


**Declaration of Performance
for product Plywood 18mm
DoP-JS-CE-18**

1	Identification code :	FILM FACED PLYWOOD, 100% FSC DUROFORM, FULL EUCA CORE, PHENOLIC GLUE EN314-2/3, 3000X1500X18MM
2	Batch-/Serial number	ALTRIPAN NV
3	Intendent use:	Internal use as structural components in Humid conditions
4	Harmonized technical specification	EN 13986:2004+A1:2015
5	Manufacturer:	Pizhou Jiangshan Wood Co.,Ltd. /Chenlou Town, Pizhou City, Jiangu, China
6	System of Assessment and verification of constancy of performance (AVCP)	2+
7	Notified boby: Certificate N	EPH 0766-CPR-427/5

8 Declared performance		
Essential characteristics	Performance	Harmonized technical specification
Bending strength parallel (N/mm ²) perpendicular (N/mm ²)	52 67	ITT According to EN 310
Bending stiffness (Modulus Elasticity) parallel (N/mm ²) perpendicular (N/mm ²)	5840 6360	
Classification according to EN636	F20/15 E40/25	EN636
Bonding quality	Class 3	ITT (EN314-1/2)
Durability (moisture resistance) (N/mm ²)	1.16	EN314-1/2 5.1.4
Moisture Content (Up to 14) (%)	15	EN 322
Density	600	EN 323
Realease of Formaldehyde	E1	EN 717-1
Reaction to fire	Declared: D-s2, d0	

The performance of the product (products) is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Signature:
Signature Date:
Position in the Company:
Company:


 August 18, 2022
 Quality Manager
 Pizhou Jiangshan Wood Co., Ltd.

Declaration of Performance
for product Plywood 15mm
DoP-JS-CE-15

1	Identification code :	FILM FACED PLYWOOD,100% FSC DUROFORM, FULL EUCA CORE,PHENOLIC GLUE EN314-2/3 ,3000X1500X15MM
2	Batch-/Serial number	ALTRIPAN NV
3	Intendent use:	Internal use as structural components in Humid conditions
4	Harmonized technical specification	EN 13986:2004+A1:2015
5	Manufacturer:	Pizhou Jiangshan Wood Co.,Ltd. /Chenlou Town,Pizhou City,Jiangsu,China
6	System of Assessment and verification of constancy of performance (AVCP)	2+
7	Notified boby:	EPH
	Certificate N	0766-CPR-427/5

8	Declared performance	
	Essential characteristics	Performance
	Bending strength parallel (N/mm2)	51
	perpendicular (N/mm2)	60
	Bending stiffness(Modulus Elasticity) parallel (N/mm2)	5750
	perpendicular (N/mm2)	6150
	Classification according to EN636	F20/15 E40/25
	Bonding quality	Class 3
	Durability (molsture resistance) (N/mm2)	1.1
	Moisture Content (Up to 14) (%)	15
	Density	600
	Realease of Formaldehyde	E1
	Reaction to fire	Declared:D-s2,d0

The performance of the product(products)is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer,identified above.
Signed for and behalf of the manufactured by:

Signature:

Signature Date:

Position in the Company:

Company:

August 18, 2022

Quality Manager

Pizhou Jiangshan Wood Co.,Ltd.




Declaration of Performance
for product Plywood 12mm
DoP-JS-CE-12

1	Identification code :	FILM FACED PLYWOOD,100% FSC DUROFORM, FULL EUCA CORE,PHENOLIC GLUE EN314-2/3 ,3000X1500X12MM
2	Batch-/Serial number	ALTRIPAN NV
3	Intendent use:	Internal use as structural components in Humid conditions
4	Harmonized technical specification	EN 13986:2004+A1:2015
5	Manufacturer:	Pizhou Jiangshan Wood Co.,Ltd. /Chenlou Town,Pizhou City,Jiangsu,China
6	System of Assessment and verification of constancy of performance (AVCP)	2+
7	Notified boby:	EPH
	Certificate N	0766-CPR-427/5

8	Declared performance		
	Essential characteristics	Performance	Harmonized technical specification
	Bending strength parallel (N/mm ²)	51	ITT According to EN 310
	perpendicular (N/mm ²)	65	
	Bending stiffness(Modulus Elasticity) parallel (N/mm ²)	5600	EN636
	perpendicular (N/mm ²)	5050	
	Classification according to EN636	F20/15 E40/25	ITT(EN314-1/2)
	Bonding quality	Class 3	EN314-1/2 5.1.4
	Durability (molsture resistance) (N/mm ²)	1.08	EN 322
	Moisture Content (Up to 14) (%)	15	EN 323
	Density	600	
	Realease of Formaldehyde	E1	EN 717-1
	Reaction to fire	Declared:D-s2,d0	

The performance of the product(products)is in conformity with the declared performance
This declaration of performance is issued the sole responsibility on the manufacturer,identified above.
Signed for and behalf of the manufactured by:

Signature:
Signature Date:
Position in the Company:
Company:


 August 18, 2022
 Quality Manager
 Pizhou Jiangshan Wood Co.,Ltd.

Declaration of Performance
for product Plywood 21mm
DoP-JS-CE-21

1	Identification code :	FILM FACED PLYWOOD,100% FSC DUROFORM, FULL EUCA CORE,PHENOLIC GLUE EN314-2/3 ,3000X1500X21MM
2	Batch-/Serial number	ALTRIPAN NV
3	Intendent use:	Internal use as structural components in Humid conditions
4	Harmonized technical specification	EN 13986:2004+A1:2015
5	Manufacturer:	Pizhou Jiangshan Wood Co.,Ltd. /Chenlou Town,Pizhou City,Jiangsu,China
6	System of Assessment and verification of constancy of performance (AVCP)	2+
7	Notified boby:	EPH
	Certificate N	0766-CPR-427/5

8	Declared performance	
	Essential characteristics	Performance
	Bending strength parallel (N/mm ²)	55
	perpendicular (N/mm ²)	68
	Bending stiffness(Modulus Elasticity) parallel (N/mm ²)	5850
	perpendicular (N/mm ²)	6400
	Classification according to EN636	F20/15 E40/25
	Bonding quality	Class 3
	Durability (moisture resistance) (N/mm ²)	1.18
	Moisture Content (Up to 14) (%)	15
	Density	600
	Realease of Formaldehyde	E1
	Reaction to fire	Declared:D-s2,d0


The performance of the product(products)is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer,identified above.
Signed for and behalf of the manufactured by:

Signature:

Signature Date:

Position in the Company:

Company:


 August 18, 2022
 Quality Manager
 Pizhou Jiangshan Wood Co.,Ltd.